

THRUVUE™ INFINITY MOTORIZED WINDOW

BUILD 3 EL ALUMINUM EXT/ ALUMINUM INT


Unit Width:	144.000"	Open angle Straight out 90°
Unit Height:	72.000"	
R.O. Width:	144.500"	
R.O. Height:	72.500"	

Approved By:


Date:

Note:

RO Width: Rough Opening width is from framing to framing
RO Height: Rough Opening height is from countertop to framing




Plan View



Section View

Exterior Elevation



Standard Glazing Specification

Glass Type	Cardinal LoE-366
IGU	1" 6mm LoE366/12.7mm
Air/6mm	Clear
Visible light transmission	=60%
Exterior reflectance	=11%
Solar heat gain coefficient	=0.28
Winter U-Value	=0.29, >34ft²

General Notes

Production Info

Build Dimensions

Unit Width	144.0000
Unit Height	72.0000
Sash Width	141.6250
Sash Height	70.3125
Glass Width	135.3750
Glass Height	64.0000
Sash Center	70.8125

Finish Schedule

Jamb Exterior	Color
Sash Exterior	Color
Jamb Interior	Color
Sash Interior	Color
Sash core/edge	Blk Anodize
Hinge Exterior	Color
Handle Exterior	N/A
Handle Interior	N/A
Motor Interior	Black
Motor Mount	Stainless
Motor Cover	Color
Drip Cap	Color
IGU Spacer	Black
Screen Track	N/A
Screen Mesh	N/A
Weather Strip	Black

Manufacturer Name and Address
OPTVUE
3204 PRODUCTION AVE
OCEANSIDE, CA 92058
+1(760) 760-0110



Customer Name	OPTVUE CUSTOMER	Sheet	1
Date	10/27/25		
Scale	-		